

Technical Data Sheet

Version 1 – October 2015

Fencelife Plus+

Five year protection for rough sawn and smooth wood.

Product Description

Water based fence treatment containing a wax enriched polymer for greater resistance to the weather and product wash off during a shower, while still allowing for recoating without worry of repulsion of additional coats.

Advantages

Low odour and VOC.
 Can be applied to both rough sawn wood (two coats) and smooth planed wood (three coats).
 Can be applied to damp wood from five hours onwards following rain.
 Showerproof in one hour.
 Provides protection for up to five years.

Typical Uses

On rough sawn or smooth planed fencing or sheds.
 Not for use on decking or garden furniture – other specific products for these.

Technical Data

| | |
|---|---|
| Colours | Cornflower; Country Oak; Dark Oak; Forest Green; Harvest Gold; Medium Oak; Red Cedar; Sage; Slate; Tudor Black Oak; Willow. |
| Sheen | Matt to Satin |
| Theoretical Spreading Rate m ² /lt | 4 to 6m ² /litre/coat, (Depending on Substrate). |
| VOC g/l | Max. 25g / l (depending on colour). |
| VOC %w/w | Max 2.5% w/w (depending on colour). |
| Storage | Store away from sunlight in a covered, cool & dry place |
| Shelf Life | At least 2 Yrs |
| In-can Appearance | Coloured structured (slightly gel-like) liquid. |
| Solubility | Fully soluble in water. |

Drying / Overcoating Times

| Temp @ 25 °C | Touch Dry 1-2 Hrs | Overcoating 4 Hrs |
|---|----------------------|----------------------|
| (To BS3900 Part C2 under normal conditions of temperature and humidity. This product will not thoroughly dry at temperatures below 5° C or under very humid conditions) | | |

Preparation

If using a sprayer, follow instructions provided.
 Remove any dirt from surface with a stiff brush.
 Stir well before use.
 Apply on a warm, dry day above 10°C.

Application and Use

| | |
|---|---|
| Application Methods | Brush Ronseal Sprayer |
| May require an additional coat(s) if applying to very weathered wood or over a very contrasting colour. | |
| Maintenance | Gives colour protection for up to five years. Inspect annually, and re-coat if areas of failure observed. |

Clean Up

Wash utensils out with warm soapy water.
Clean up any drips onto plants, paving, etc with water straight away.
Ensure container is fully re-sealed after use.
Some local authorities have special facilities for disposing of waste products. Do not empty into drains or water courses.

Important Notes

Avoid the inhalation of dust when sanding, wear a suitable face mask or employ wet sanding techniques.
Always conduct a test area to confirm colour suitability.
Do not apply in temperatures below 10°C or in conditions of high humidity

Health & Safety

Observe and follow all warnings and instructions for use shown on the pack/product label

Refer to Material Safety datasheet for full details of first aid, fire fighting, accidental release, handling, exposure controls/P.P.E and disposal

Disclaimer

Whilst these specifications are based on expert technical knowledge and practical experience it is for guidance only & given in good faith but without warranty. Users should first carry out their own trials to ascertain the suitability of the product for their intended application and surface, as we cannot assume responsibility for any work as the ultimate result depends on factors out of our control.
The user must also be satisfied that of the suitability of the product in circumstances other than those set out in this data sheet. The user should also maintain appropriate control procedures.
Should further information be required please contact our Technical Services Dept.

Information & Services

Sherwin-Williams Diversified Brands Ltd operates a quality management system that complies with the requirements of ISO 9000:2008 (Certificate No. FM 01669). Sherwin-Williams Diversified Brands Ltd operates an Environmental Management System that complies with the requirements of ISO 14001:2004 (Certificate No. EMS 35924).

Sherwin-Williams Diversified Brands Limited.
Thornccliffe Park, Chapelton, Sheffield S35 2YP
Tel: +44 (0)114 246 7171 Fax: +44 (0)114 245 5629
Registered in England 2968830

Sherwin-Williams.co.uk

